





THE RIGHT FILTER FOR EVERY CIRCUMSTANCE



STANDARD M CLASS **FILTER**

FINE DUST, GRANULES, SOLID AND DRY SWARF



M CLASS TEFLON FILTER

FINE DUST, GRANULES, WET OR DUMP SWARF AND SOLID MATERIALS. ESPECIALLY SUITABLE FOR STICKY DUST.




FINE DUST, GRANULES, SWARF AND SOLID MATERIALS THAT TEND TO BECOME ELECTROSTATICALLY CHARGED. STANDARD ON THE MODELS IN THE ATEX RANGE.



M CLASS PTFE FILTER

VERY FINE AND STICKY DUST. HYGROSCOPIC AND WET MATERIALS. **FOOD CERTIFIED**



TEMPERATURES UP TO 250°C.



HYGROSCOPIC MATERIALS THAT TEND TO

DUST AND SOLID MATERIALS WITH



M CLASS ANTISTATIC PTFE FILTER

BECOME ELECTROSTATICALLY CHARGED. STANDARD ON THE MODELS IN THE ATEX RANGE, FOOD CERTIFIED.






M CLASS - FILTRATION EFFICIENCY 1μ (EN60335269) FILTER SURFACE UP TO 40.000 cm² JETCLEAN® FILTER CLEANING SYSTEM ANTISTATIC POLYESTER ALUMINATED FILTER **ESPECIALLY SUITED FOR DRY, FINE AND VERY FINE DUST**



EFFICIENCY 99,995% VERY FINE, DANGEROUS DUST WITH GRANULOMETRY <1 µ

CLASS H14 EN - 1822

ABSOLUTE FILTER



THE MATERIAL ENTERS THE CHAMBER FROM THE SUCTION INLET (1) AND THANKS TO THE CYCLONE (2) IT LOSES SPEED, SETTLING INSIDE THE VACUUM'S BIN (3). THIS WAY 90% OF THE MATERIAL IS CLEARED, GRANTING A LONGER LIFE FOR THE FILTER.

THE CYCLONE





STANDARD M CLASS FILTER

THE M CLASS FILTER HAS A FILTRATION EFFICIENCY OF 1µ, ALLOWING TO VACUUM **EVEN FINER DUST IN COMPLETE SAFETY**



VACUUM CLEANERS WITH JETCLEAN® SYSTEM

COMPACT DURABLE SAFE

- Semi-Automatic filter cleaning system
- All the filters are certified M Class
- Up to 3 motors
- Powerful, Compact and Durable
- Ideal for fine and dry dust
- Practical Detachable Bin
- Up To 100 Lt Capacity
- Available With Longopac®









	XM 20	JETCLEAN	XM 35	JETCLEAN	XM 35 .	JETCLEAN LP		M 65 JETCLEAN		M 100 JETCLEAN LP
MOTORS		2		2		2		3		3
POWER	kW-HP	2,6 - 3,5	kW-HP	2,6 - 3,5	kW-HP	2,6 - 3,5	kW-HP	3,9 - 5,2	kW-HP	3,9 - 5,2
VOLTAGE FREQUENCY	V Hz	230/50-60	V Hz	230/50-60	V Hz	230/50-60	V Hz	230/50-60	V Hz	230/50-60
MAXIMUM VACUUM	mBar	250	mBar	250	mBar	250	mBar	250	mBar	250
MAXIMUM AIR FLOW	m³/h	380	m³/h	380	m³/h	380	m³/h	570	m³/h	570
INLET	Ø mm	50	Ø mm	50	Ø mm	50	Ø mm	50	Ø mm	50
FILTER SURFACE	cm²	34.000	cm²	40.000	cm ²	40.000	cm²	40.000	cm²	40.000
CAPACITY	Lt	20	Lt	45		LONGOPAC®	Lt	65/100		LONGOPAC®



FILTER CARTRIDGE

WITH STANDARD M CLASS FILTER AND SEMI-AUTOMATIC JETCLEAN® FILTER CLEANING SYSTEM



ABSOLUTE FILTER

AVAILABLE FOR THE WHOLE RANGE



SLIDING DAMPER

AVAILABLE FOR ALL MODELS



UP TO THREE YEARS WARRANTY

VACUUM CLEANERS WITH POCKET FILTER

POWERFUL VERSATILE RELIABLE

- Manual Filter Shaker
- All the Filters are certified M Class
- Up to 3 motors
- Sturdy, Safe, suitable for every need
- Ideal for Dust, Granules and Swarf
- Practical detachable Bin
- Up To 100 Lt Capacity
- Available With Longopac®







		MINIBULL		M 65 / 100		BULL UNO 2 M / 3M
MOTORS		2		3		2/3
POWER	kW-HP	2,6 - 3,5	kW-HP	3,9 - 5,2	kW-HP	2,6 - 3,5 / 3,9 - 5,2
VOLTAGE FREQUENCY	V Hz	230 / 50 - 60	V Hz	230 / 50 - 60	V Hz	230 / 50 - 60
MAXIMUM VACUUM	mBar	250	mBar	250	mBar	250
MAXIMUM AIR FLOW	m³/h	380	m³/h	570	m³/h	380 / 570
INLET	Ø mm	70	Ø mm	70	Ø mm	80
FILTER SURFACE	cm²	15.000	cm²	24.000 / 38.000	cm ²	24.000 / 38.000
CAPACITY	Lt	45	Lt	65 / 100	Lt	65 / 100



STANDARD M CLASS POCKET FILTER **SUITABLE FOR EVERY NEED**















ABSOLUTE FILTER AVAILABLE FOR THE WHOLE RANGE



SP SYSTEM

AUTOMATIC REVERSE AIR JET FILTER CLEANING. AVAILABLE ON DEMAND.



UP TO THREE YEARS WARRANTY

WD VACUUM CLEANER FOR LIQUIDS

		WD 132	WD 132 P	WD 133
MOTORS		2	2	3
POWER	kW-HP	2,6-3,5	2,6 - 3,5	3,9 - 5,2
VOLTAGE FREQUENCY	V Hz	230/50-60	230/50-60	230/50-60
MAXIMUM VACUUM	mBar	250	250	250
MAXIMUM AIR FLOW	m³/h	380	380	570
INLET	Ø mm	70	70	70
CAPACITY	Lt	130	130	130
DISCHARGE SYSTEM		discharge by gravity	automatic discharge by pump	discharge by gravity
THE PARTY OF THE P	The State of the last	100000000000000000000000000000000000000		

FLOATING SYSTEM

FOR LIQUIDS

STANDARD FILTER STANDARD FILTER **FOR DUST**







BATTERY POWERED VACUUM CLEANER

		BULL 24	FOX 24
MOTORS		3	3
POWER	kW-HP	1,5/2	1,5/2
VOLTAGE FREQUENCY	V	24	24
MAXIMUM VACUUM	mBar	240	240
MAXIMUM AIR FLOW	m³/h	350	350
INLET	Ø mm	80	80
BATTERY	N°	2	4
UPTIME	h	1	2
	LACACO I	THE RESERVE OF THE PARTY OF THE	1000





DEPURECO

ACCESSORIES

CONVENIENT SOLUTIONS TO HELP YOU WITH YOUR WORK







BIN EMPTYING KIT



LONGOPAC® SEPARATOR



WET & DRY



TILTABLE 580 LT

THE RIGHT ACCESSORY FOR EVERY NEED



DOUBLE BEND TUBE



ANTISTATIC RUBBER





FLOOR BRUSH WITH BRISTLES



CONIC SECTION



PVC ROUND BRUSH



FLOOR SQUEEGEE WITH RUBBER STRIPS



PIPE WITH HANDLE



ANTISTATIC



ANTISTATIC BRUSH WITH BRASS BRISTLES



SILICONE CONIC

SECTION

ANTISTATIC BENT RUBBER CONE



PIPE CLEANING BRUSH



ANTISTATIC FLAT PIPE

FLEXIBLE HOSES FOR ALL MATERIALS



BLACK EVAFLEX HOSE



BLACK EVAFLEX ELECTROCONDUCTIVE HOSE



POLYURETHANE



REINFORCED ABRASIVE PROOF **POLYURETHANE FLEXIBLE HOSE**



ANTISTATIC POLYURETHANE **FLEXIBLE HOSE**

